

NJRL Datasheet

This compact and efficient screw feeder is designed to streamline your production process by presenting screws with precision and speed. The feeders are compatible with a diverse range of screw types incl. non-magnetic screws, making it a versatile solution for various assembly applications. This feeder are used together with SDV-series screwdriver tools.

- Feed 1 screw pr. seconds
- Feeds M2 to M5 screws
- For screws made of any material, even non-magnetisable
- For all recess types
- Adjustable rail vibration amplitude and frequency



Supports Pan/button head, cylinder & counter sunk screws

Screw feeder	Screw size (mm)	Screw length		Screw capacity	Screw cycle time	Weight		Operating temperatur		Size (mm) WxDxH		
		(mm)	(inch)			kg	lbs	0-40°C	32-104°F			
NJRL-2320	φ2.0	3.2~25	0.13~0.98	150 cc	0.9 sec	4.2 kg	9.25 lbs	0-40°C	32-104°F	134	274	139
NJRL-2323	φ2.3	3.7~25	0.15~0.98	150 cc								
NJRL-2326	φ2.6	4.2~25	0.17~0.98	150 cc								
NJRL-2330	φ3.0	4.8~25	0.19~0.98	150 cc								
NJRL-4535	φ3.5	5.6~25	0.22~0.98	150 cc								
NJRL-4540	φ4.0	6.4~25	0.25~0.98	150 cc								
NJRL-4550	φ5.0	8.0~25	0.32~0.98	150 cc								
NJRL-4560	φ6.0	8.0~25	0.32~0.98	150 cc								

Compatible with washer thickness 0.4 to 1.0 mm.
Compatible with all screw types

Future of Assembly